


UL 325 2018 COMPLIANT

UL 991 COMPLIANT





INTEGRATED BATTERY BACKUP

.....

850-942-1003

MAINTENANCE FREE BRUSHLESS DC MOTOR

> PRE-WIRED LOOP DETECTOR RACK

MECHANICAL FOOT PEDAL RELEASE

SLIDE GATE OPERATOR



Mechanical Foot Pedal Release

Ŵ

COMPACT, LOW PROFILE FRAME

RESIDENTIAL & COMMERCIAL APPLICATIONS

SLIDERS | SWINGERS | OVERHEADS The standard by which all other automatic gate operators are measured





## SLIDE GATE OPERATOR





MECHANICAL FOOT PEDAL RELEASE



BRUSHLESS DC MOTOR CONTINUOUS DUTY 24V 1HP



## CONTROL BOARD WITH ARRAY OF FEATURES



## NOW WITH BIGGER INTERNAL DISCONNECT GEARBOX





## UL 325 2018 Compliant

| OL 323 2018 Compliant    |   |
|--------------------------|---|
| Max Gate Welght          | 1,600 lbs.                                      |
| Max Gate Length          | 50 feet   |
| Warranty                 | 7 year residential - 5 year commercial          |
| Motor                    | 24 VDC brushless - 1/2 HP motor                 |
| Gate Speed               | 12" per second                                  |
| Power Options            | 115/230 VAC single phase and 24 VDC solar panel |
| Duty Cycle               | Continuous                                      |
| Battery Back Up          | Integrated, with (2) 7Ah 12VDC batteries        |
| Battery Back Up Capacity | 150 cycles on a 1,000 lb. gate                  |
| Temperature Range        | -40 to 160°                                     |
| Gearbox Ratio            | 20:1 with internal disconnect                   |
| Width X Length X Height  | 15.5" X 18.5" X 16"                             |
| Shipping Weight          | 95 lbs.   |
| Emergency Release        | Mechanical foot pedal release                   |
| Belt Size                | 4L-230 (AX21)                                   |
| Main Sprocket Size       | 41B22X7/8                                       |
| Chain Size               | 41NP (20' included)                             |
| Gearbox Sprocket         | N/A   |
| Limit Shaft Sprocket     | 41B15X5/8                                       |
| Breaker Requirement      | 20 amp dedicated                                |
| Gearbox Pulley           | 2 ½" with 5/8" bore                             |
| Motor Pulley             | 2" with 5/8" bore                               |

The Warrantor warrants All SL-90 DC Gate Operators. ALL-O-MATIC INC warrants its gate openers for a period of five (5) years in commercial installations, and for a period of seven (7) years in residential installation to be free from defects in circuitry, motor, gear box and workmanship. This warranty applies from the date of purchase to the original owner. Warrantor will repair or, at its option, replace any device which it finds to require service. This device must be sent to the warrantor at the consumer's expense. The warrantor will return the repaired or replaced unit to the customer at the consumer's expense. Labor charges for dealer service or replacement are the responsibility of the owner. These warranties are in lieu of all other warranties either expressed or implied, and ALL-O-MATIC INC shall not be liable for consequential damage. All implied warranties of merchantability and or fitness for a particular purpose are hereby disclaimed and excluded. This limitation is not valid in jurisdictions which do not allow limitation of incidental or consequential damages or limitation of warranty periods. Caution in order to obtain this policy, please complete the registration card and send it by mail within 30 days of purchasing from ALL-O-MATIC INC. or your INSTALLER. If not registered only a one year warranty on all parts will be provided.



SLIDERS | SWINGERS | OVERHEADS The standard by which all other **automatic gate operators** are measured

5159 Woodlane Circle Tallahassee, FI 32303 www.BTFencing.com